

# Auto Feeding & Inspection System AFS-800S



# **Product description**

The automation of SMT industry has evolved continuously ,however,not much progress has been made with regard to Error blocking on changing SMT component reels/employee outflow/Low pass rate with manual splicing,Moreover with the gradual integration of electronic components,Ultra small materials are used more extensively,conventional quality inspection approaches can not satisfy the demand.The world's first BLUIRIS AFS-800S Machine has been developed as a solution to the challenge,it helps to improve outgoing quality,satisfy management via information system,achieve higher productivity and reduce operating cost.

1.Real time error blocking when SMT feeding

2.Increase productivity
4.Auto Measure and Judge
5.Improve quality

**PRODUCT BENEFITS:** 6. Standardize the strict process 7. Accurate traceability

8. Satisfy splicing reliability

9. Validation function available in both stand-alone and online mode

10. Save components by unique vision inspection technology

#### 1. Intelligent recognition for both tape and component:

Size and specification determination, Empty – Pocket detection, Pitch matching, Precise cutting, done by machine automatically to realize error proofing.



8mm(Paper and Plastic applicable)

#### 3.Auto Tape splicing:

Dedicated 8mm carrier tape splicing ,First Pass Yield at 99.5% or above.

#### 4. Multiple Function:

Splicing Mode;

Measuring Mode:

Measuring &Splicing Mode;

5. Error proofing system via Multiple Bar code Verification:

(Machine/Table /Station/Feeder /Old Reel/New Reel/Employee Badge etc) as perfect guarantee.

- 6. Capable for MES integration(Optional), connectivity via Wi-Fi for managing the operation systematically and integrating traceability information, More Intelligent.
- 7. Mobile operation for flexible deployment on SMT lines.
- 8. Intuitive and easy to use ,operator can handle the machine in 30mins' training.









# **AFS-800S Specifications**



#### **Camera Parameters**

Power: DC24V

Illuminant: LED

Resolution: 1.3 Mega pixels

## **Battery Parameters**

Power Supply: DC24V, 60AH

Power Adapter: AC220V, 10A

#### Barcode scanner

Model: QR Code DS2278 Or

Barcode LI4278

Power: 5.2V-1.1A

#### **Basic Info**

Product: Auto Feeding & Inspection System

Model: AFS-800S

Color: Gray & White

Machine size: 560(L)\*557(W)\*1320(H) mm

Weight: 130 KG

Environment: Temperature:  $10 \sim 35^{\circ}$ ;

Humidity:20% ~ 80%

## **Computer Parameters**

Operation System: WIN7/WIN10

Memory: 8G

Hard Disk: SSD 256G/512G

Monitor: 10.4 inch capacitive touch screen

#### **LCR Meter Parameters**

Model: BLUIRIS 6230D

Power Supply: DC 24V (±10%)

Test frequency Range: 20Hz~300kHz

R/C Minimum: R  $0.1\Omega$ ; C 0.1pf

Test Accuracy: 0.05%

Measurement L 0.01nH~9.9999kH display range: C 0.00001pF~9.9999F

R  $0.01m\Omega \sim 19.999M\Omega$ 

Communication Interface: RS-232C

## **System Parameter**

Worktable height: 900mm ± 50mm

Tape: 8mm(Paper and Plastic applicable)

Test component: 01005/0201/0402/0603/ 0805/1206(1210) (Paper/Plastic 4 probes are

installed in the machine)

Test Accuracy: 0.05%

Operating Voltage: DC24V

Low Power Alarm: < 30%

# Some partners







Desaysv



Longcheer



**LENS** 



**DBG** 



HUAQIN



Edifier



Blueway



**ZOWEE** 



SCD



**AMT** 



Innolux





# SHENZHEN BLUIRIS TECHNOLOGY CO.,LTD

Add: No.6 Blk.2, Honghui High-tech Park, Liuxian 2 Road,

Baoan, Shenzhen, China

Tel: +86-0755-23216393 \ +86-0755-83360400

Web: www.bluiris.cn

Email: marketing@bluiris.cn



Follow Bluiris WeChat Official

## Bluiris Suzhou Office

Add: Unit 15/16, 6th Floor, Building A, Tengfei Xinsu Industrial Square, No. 5 Xinghan Street, Suzhou Industrial Park

Tel: +86-0512-67158362 Phone: +86-18115501415